

**Description**

Diameter: 13/64", steel corrosion resisting band

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS21919WCF30
Minimum Qty (MOQ):	10 EA
NSN:	5340-01-320-5061
Schedule B:	7318.15.2091
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi

NO IMAGE  
AVAILABLE

## P/N MS21919WCF30 Specifications

<b>Tongue Hole Type:</b>	Round, Unthreaded
<b>Cushioning Environmental Protection:</b>	Fuel Resistant
<b>Overall Width:</b>	0.490 Inches Minimum And 0.510 Inches Maximum
<b>Diameter:</b>	0.199 Inches Minimum And 0.209 Inches Maximum
<b>Material Thickness:</b>	0.032 Inches Nominal
<b>Center To Center Distance Between Loop And Mounting Hole:</b>	1.390 Inches Minimum And 1.420 Inches Maximum
<b>Distance From Loop Center To Tongue End:</b>	1.623 Inches Nominal
<b>Loop Inside Diameter:</b>	1.860 Inches Minimum And 1.890 Inches Maximum
<b>Material:</b>	Rubber Synthetic Cushion
<b>Material:</b>	Steel Corrosion Resisting Band
<b>Material Document And Classification:</b>	Ams 3215 Assn Std Single Material Response Cushion
<b>Material Document And Classification:</b>	Ams 5510 Assn Std Single Material Response Band
<b>Surface Treatment:</b>	Passivate Band
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Band
<b>Style Designator:</b>	Offset Mount

## How to Order

Order this clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919WCF30> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.