P/N MS21919WCG2

Description

Diameter: 13/64", steel comp 321 band, MS21919 series clamp

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21919WCG2
Minimum Qty (MOQ):	10
NSN:	5340-01-160-2304
Schedule B:	7318.15.5030
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9

* See page 2 for technical characteristics

P/N MS21919WCG2 Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Weather Resistant
Overall Width:	0.375 Inches Nominal
Diameter:	0.199 Inches Minimum And 0.209 Inches Maximum
Material Thickness:	0.032 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	0.442 Inches Minimum And 0.472 Inches Maximum
Distance From Loop Center To Tongue End:	0.645 Inches Nominal
Loop Inside Diameter:	0.110 Inches Minimum And 0.140 Inches Maximum
Special Features:	Cushion Ozone Resistant
Material:	Rubber Chloroprene Class Cr Cushion
Material:	Steel Comp 321 Band
Material Document And Classification:	Ams 3209 Assn Std Single Material Response Cushion
Material Document And Classification:	Ams 5510 Assn Std Single Material Response Band
Surface Treatment:	Passivate Band
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Band

How to Order

Order this loop clamp from our inventory online by visiting https://military-fasteners.com/clamps/loop+clamps/MS21919WCG2 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.