

P/N MS21919WCG27

Military-Fasteners.com

Description

Diameter: 13/64", steel comp band

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

| SKU / Model: | MS21919WCG27 |
|-------------------------|-----------------------|
| Minimum Qty (MOQ): | 10 |
| NSN: | 5340-01-196-0276 |
| Schedule B: | 7318.15.5030 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi |



P/N MS21919WCG27 Specifications

| Tongue Hole Type: | Round, Unthreaded |
|---|--|
| Cushioning Environmental Protection: | Weather Resistant And Ozone Resistant |
| Overall Width: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Diameter: | 0.199 Inches Minimum And 0.209 Inches Maximum |
| Material Thickness: | 0.032 Inches Nominal |
| Center To Center Distance Between Loop And Mounting Hole: | 1.297 Inches Minimum And 1.327 Inches Maximum |
| Distance From Loop Center To Tongue End: | 1.515 Inches Minimum And 1.545 Inches Maximum |
| Loop Inside Diameter: | 1.673 Inches Minimum And 1.703 Inches Maximum |
| Material: | Rubber Chloroprene Class Cr Cushion |
| Material: | Steel Comp 321 Band |
| Material Document And Classification: | Ams 3209 Assn Std Single Material Response Cushion |
| Material Document And Classification: | Ams 5510 Assn Std Single Material Response Band |
| Surface Treatment: | Passivate Band |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Band |
| Style Designator: | Offset Mount |

How to Order

Order this loop clamp from our inventory online by visiting <u>https://military-fasteners.com/clamps/loop+clamps/MS21919WCG27</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.