

Description

Diameter: 13/64", steel comp 321 band, MS21919 series clamp

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|------------------------------------|
| SKU / Model: | MS21919WCG4 |
| Minimum Qty (MOQ): | 20 |
| NSN: | 5340-01-146-7422 |
| Schedule B: | 7318.15.2091 |
| ECCN: | EAR99 |
| National Motor Freight: | 013120, Aluminum Article Noi Sub 6 |



* See page 2 for technical characteristics

P/N MS21919WCG4 Specifications

| | |
|------------------------------------------------------------------|----------------------------------------------------|
| Tongue Hole Type: | Round, Unthreaded |
| Cushioning Environmental Protection: | Weather Resistant |
| Overall Width: | 0.365 Inches Minimum And 0.385 Inches Maximum |
| Diameter: | 0.199 Inches Minimum And 0.209 Inches Maximum |
| Material Thickness: | 0.032 Inches Nominal |
| Center To Center Distance Between Loop And Mounting Hole: | 0.514 Inches Minimum And 0.544 Inches Maximum |
| Distance From Loop Center To Tongue End: | 0.717 Inches Nominal |
| Loop Inside Diameter: | 0.235 Inches Minimum And 0.265 Inches Maximum |
| Special Features: | Cushion Also Ozone Resistant |
| Material: | Rubber Chloroprene Class Cr Cushion |
| Material: | Steel Comp 321 Band |
| Material Document And Classification: | Ams 3209 Assn Std Single Material Response Cushion |
| Material Document And Classification: | Mil-s-6721 Mil Spec Single Material Response Band |
| Surface Treatment: | Passivate Band |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Band |
| Style Designator: | Offset Mount |

How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919WCG4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.