

## Description

Diameter: 13/64", steel comp 321 band, MS21919 series clamp

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS21919WCG4
Minimum Qty (MOQ):	20
NSN:	5340-01-146-7422
Schedule B:	7318.15.2091
ECCN:	EAR99
National Motor Freight:	013120, Aluminum Article Noi Sub 6



## P/N MS21919WCG4 Specifications

<b>Tongue Hole Type:</b>	Round, Unthreaded
<b>Cushioning Environmental Protection:</b>	Weather Resistant
<b>Overall Width:</b>	0.365 Inches Minimum And 0.385 Inches Maximum
<b>Diameter:</b>	0.199 Inches Minimum And 0.209 Inches Maximum
<b>Material Thickness:</b>	0.032 Inches Nominal
<b>Center To Center Distance Between Loop And Mounting Hole:</b>	0.514 Inches Minimum And 0.544 Inches Maximum
<b>Distance From Loop Center To Tongue End:</b>	0.717 Inches Nominal
<b>Loop Inside Diameter:</b>	0.235 Inches Minimum And 0.265 Inches Maximum
<b>Special Features:</b>	Cushion Also Ozone Resistant
<b>Material:</b>	Rubber Chloroprene Class Cr Cushion
<b>Material:</b>	Steel Comp 321 Band
<b>Material Document And Classification:</b>	Ams 3209 Assn Std Single Material Response Cushion
<b>Material Document And Classification:</b>	Mil-s-6721 Mil Spec Single Material Response Band
<b>Surface Treatment:</b>	Passivate Band
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Band
<b>Style Designator:</b>	Offset Mount

## How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919WCG4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.