

Description

Diameter: 7/8", loop type, cushioned, corrosion resistant steel with silicone cushion

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[AS21919WCH14](#)

| | |
|-------------------------|-----------------------------|
| SKU / Model: | MS21919WCH14 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5340-01-140-5708 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |



* See page 2 for technical characteristics

P/N MS21919WCH14 Specifications

| | |
|--|---|
| Tongue Hole Type: | Round, Unthreaded |
| Cushioning Environmental Protection: | Corrosion Resistant And Weather Resistant And Oil Resistant |
| Overall Width: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Diameter: | 0.199 Inches Minimum And 0.209 Inches Maximum |
| Material Thickness: | 0.032 Inches Nominal |
| Center To Center Distance Between Loop And Mounting Hole: | 0.874 Inches Minimum And 0.904 Inches Maximum |
| Distance From Loop Center To Tongue End: | 1.107 Inches Nominal |
| Loop Inside Diameter: | 0.860 Inches Minimum And 0.890 Inches Maximum |
| Material: | Rubber Silicone Class Q Cushion |
| Material: | Steel Comp 321 Band |
| Material Document And Classification: | Ams 3303 Assn Std Single Material Response Cushion |
| Material Document And Classification: | Mil-s-6721 Mil Spec Single Material Response Band |
| Surface Treatment: | Passivate Band |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Band |
| Style Designator: | Offset Mount |

How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919WCH14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.