

Description

1-3/16" diameter, loop type clamp, cushioned, corrosion resistant steel with silicone cushion

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------------|
| SKU / Model: | MS21919WCH19 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5340-01-156-7311 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |

NO IMAGE
AVAILABLE

P/N MS21919WCH19 Specifications

| | |
|--|--|
| Tongue Hole Type: | Round, Unthreaded |
| Cushioning Environmental Protection: | Corrosion Resistant And Weather Resistant And Oil Resistant |
| Overall Width: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Diameter: | 0.199 Inches Minimum And 0.209 Inches Maximum |
| Material Thickness: | 0.032 Inches Nominal |
| Center To Center Distance Between Loop And Mounting Hole: | 1.046 Inches Minimum And 1.076 Inches Maximum |
| Distance From Loop Center To Tongue End: | 1.279 Inches Nominal |
| Loop Inside Diameter: | 1.173 Inches Minimum And 1.203 Inches Maximum |
| Special Features: | Cushion Color White |
| Material: | Rubber Silicone Class Q Cushion |
| Material: | Steel Comp 302 Band Or Steel Comp 321 Band |
| Material Document And Classification: | Mil-s-5059 Mil Spec 1st Material Response Band Or Ams 5510 Assn Std 2nd Material Response Band |
| Surface Treatment: | Passivate Band |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Band |
| Style Designator: | Offset Mount |

How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919WCH19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.