

**Description**

diameter: 1/4", loop type, cushioned, corrosion resistant steel with silicone cushion

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS21919WCH4
Minimum Qty (MOQ):	20
NSN:	5340-01-140-0925
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



\* See page 2 for technical characteristics

## P/N MS21919WCH4 Specifications

<b>Tongue Hole Type:</b>	Round, Unthreaded
<b>Cushioning Environmental Protection:</b>	Corrosion Resistant And Weather Resistant And Oil Resistant
<b>Overall Width:</b>	0.365 Inches Minimum And 0.385 Inches Maximum
<b>Diameter:</b>	0.199 Inches Minimum And 0.209 Inches Maximum
<b>Material Thickness:</b>	0.032 Inches Minimum
<b>Center To Center Distance Between Loop And Mounting Hole:</b>	0.614 Inches Minimum And 0.644 Inches Maximum
<b>Distance From Loop Center To Tongue End:</b>	0.817 Inches Nominal
<b>Loop Inside Diameter:</b>	0.235 Inches Minimum And 0.265 Inches Maximum
<b>Material:</b>	Rubber Silicone Class Q Cushion
<b>Material:</b>	Steel Comp 321 Band
<b>Material Document And Classification:</b>	Ams 3303 Assn Std Single Material Response Cushion
<b>Material Document And Classification:</b>	Mil-s-6721 Mil Spec Single Material Response Band
<b>Surface Treatment:</b>	Passivate Band
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Band
<b>Style Designator:</b>	Offset Mount

## How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919WCH4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.