

**Description**

Diameter: 3/8", loop type, cushioned, corrosion resistant steel with silicone cushion, MS21919 series clamp

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS21919WCH6
Minimum Qty (MOQ):	20
NSN:	5340-01-142-4469
Schedule B:	7318.15.2091
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



\* See page 2 for technical characteristics

## P/N MS21919WCH6 Specifications

<b>Tongue Hole Type:</b>	Round, Unthreaded
<b>Cushioning Environmental Protection:</b>	Heat
<b>Overall Width:</b>	0.375 Inches Nominal
<b>Diameter:</b>	0.204 Inches Nominal
<b>Material Thickness:</b>	0.0285 Inches Minimum And 0.0355 Inches Maximum
<b>Center To Center Distance Between Loop And Mounting Hole:</b>	0.592 Inches Nominal
<b>Distance From Loop Center To Tongue End:</b>	0.780 Inches Nominal
<b>Loop Inside Diameter:</b>	0.360 Inches Minimum And 0.390 Inches Maximum
<b>Special Features:</b>	Cushion Color White
<b>Material:</b>	Rubber Silicone Class Q Cushion
<b>Material:</b>	Steel Comp 302 Band Or Steel Comp 321 Band
<b>Material Document And Classification:</b>	Ams 3303 Assn Std Single Material Response Cushion
<b>Material Document And Classification:</b>	Mil-s-5059 Mil Spec 1st Material Response Band Or Ams 5510 Assn Std 2nd Material Response Band
<b>Style Designator:</b>	Offset Mount

## How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919WCH6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.