

Description

Diameter: 13/16", loop type, cushioned, corrosion resistant steel with fluorosilicone cushion

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------------|
| SKU / Model: | MS21919WCJ13 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5340-00-165-7671 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |



* See page 2 for technical characteristics

P/N MS21919WCJ13 Specifications

| | |
|--|--|
| Tongue Hole Type: | Round, Unthreaded |
| Cushioning Environmental Protection: | Heat And Hydraulic Fluid |
| Overall Width: | 0.500 Inches Nominal |
| Diameter: | 0.204 Inches Nominal |
| Material Thickness: | 0.029 Inches Minimum And 0.036 Inches Maximum |
| Center To Center Distance Between Loop And Mounting Hole: | 0.858 Inches Nominal |
| Distance From Loop Center To Tongue End: | 1.076 Inches Nominal |
| Loop Inside Diameter: | 0.813 Inches Nominal |
| Material: | Rubber Fluorocarbon Class Fpm Cushion |
| Material: | Steel Comp 321 Band Or Steel Comp 347 Band |
| Material Document And Classification: | Mil-g-23652 Mil Spec Single Material Response Cushion Or Mil-r-25897 Mil Spec Single Material Response Cushion |
| Material Document And Classification: | Mil-s-6721 Mil Spec All Material Responses Band |
| Surface Treatment: | Passivate Band |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Band |
| Style Designator: | Offset Mount |

How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919WCJ13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.