

Description

diameter: 7/8", loop type, cushioned, corrosion resistant steel with fluorosilicone cushion

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21919WCJ14
Minimum Qty (MOQ):	10
NSN:	5340-01-143-9255
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



P/N MS21919WCJ14 Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Oil Resistant And Fuel Resistant
Overall Width:	0.490 Inches Minimum And 0.510 Inches Maximum
Diameter:	0.204 Inches Nominal
Material Thickness:	0.032 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	0.874 Inches Minimum And 0.904 Inches Maximum
Distance From Loop Center To Tongue End:	1.107 Inches Nominal
Loop Inside Diameter:	0.860 Inches Minimum And 0.890 Inches Maximum
Material:	Rubber Fluorosilicone Class Fq Cushion
Material:	Steel Comp 321 Band
Material Document And Classification:	Mil-r-25988,type 2,class 1,grade 60 Mil Spec Single Material Response Cushion
Material Document And Classification:	Mil-s-6721 Mil Spec Single Material Response Band
Surface Treatment:	Passivate Band
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Band
Style Designator:	Offset Mount

How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919WCJ14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.