

**Description**

diameter: 7/8", loop type, cushioned, corrosion resistant steel with fluorosilicone cushion

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS21919WCJ14
Minimum Qty (MOQ):	10
NSN:	5340-01-143-9255
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



## P/N MS21919WCJ14 Specifications

<b>Tongue Hole Type:</b>	Round, Unthreaded
<b>Cushioning Environmental Protection:</b>	Oil Resistant And Fuel Resistant
<b>Overall Width:</b>	0.490 Inches Minimum And 0.510 Inches Maximum
<b>Diameter:</b>	0.204 Inches Nominal
<b>Material Thickness:</b>	0.032 Inches Nominal
<b>Center To Center Distance Between Loop And Mounting Hole:</b>	0.874 Inches Minimum And 0.904 Inches Maximum
<b>Distance From Loop Center To Tongue End:</b>	1.107 Inches Nominal
<b>Loop Inside Diameter:</b>	0.860 Inches Minimum And 0.890 Inches Maximum
<b>Material:</b>	Rubber Fluorosilicone Class Fq Cushion
<b>Material:</b>	Steel Comp 321 Band
<b>Material Document And Classification:</b>	Mil-r-25988,type 2,class 1,grade 60 Mil Spec Single Material Response Cushion
<b>Material Document And Classification:</b>	Mil-s-6721 Mil Spec Single Material Response Band
<b>Surface Treatment:</b>	Passivate Band
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Band
<b>Style Designator:</b>	Offset Mount

## How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919WCJ14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.