

**Description**

1/8" diameter, loop type clamp, cushioned, corrosion resistant steel with fluorosilicone cushion

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS21919WCJ2
Minimum Qty (MOQ):	10
NSN:	5340-01-188-1845
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



\* See page 2 for technical characteristics

## P/N MS21919WCJ2 Specifications

<b>Tongue Hole Type:</b>	Round, Unthreaded
<b>Cushioning Environmental Protection:</b>	Oil Resistant And Fuel Resistant
<b>Overall Width:</b>	0.365 Inches Minimum And 0.385 Inches Maximum
<b>Diameter:</b>	0.199 Inches Minimum And 0.209 Inches Maximum
<b>Material Thickness:</b>	0.032 Inches Nominal
<b>Center To Center Distance Between Loop And Mounting Hole:</b>	0.442 Inches Minimum And 0.472 Inches Maximum
<b>Distance From Loop Center To Tongue End:</b>	0.675 Inches Nominal
<b>Loop Inside Diameter:</b>	0.110 Inches Minimum And 0.140 Inches Maximum
<b>Special Features:</b>	Cushion Color Blue
<b>Material:</b>	Rubber Fluorosilicone Class Fq Cushion
<b>Material:</b>	Steel Comp 321 Band
<b>Material Document And Classification:</b>	Ams 5510 Assn Std Single Material Response Band
<b>Material Document And Classification:</b>	Mil-r-25988,ty2,cl1,gr60 Mil Spec Single Material Response Cushion
<b>Surface Treatment:</b>	Passivate Band
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Band
<b>Style Designator:</b>	Offset Mount

## How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919WCJ2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.