

P/N MS21919WCJ42

Military-Fasteners.com

Description

Diameter: 13/64", steel comp 321 band

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

| SKU / Model: | MS21919WCJ42 |
|-------------------------|-----------------------|
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5340-01-160-0395 |
| Schedule B: | 7318.15.2091 |
| ECCN: | 9A991 |
| National Motor Freight: | 095190, Hardware, Noi |



P/N MS21919WCJ42 Specifications

| Tongue Hole Type: | Round, Unthreaded |
|---|---|
| Cushioning Environmental Protection: | Oil Resistant And Fuel Resistant |
| Overall Width: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Diameter: | 0.199 Inches Minimum And 0.209 Inches Maximum |
| Material Thickness: | 0.040 Inches Nominal |
| Center To Center Distance Between Loop And Mounting Hole: | 1.773 Inches Minimum And 1.803 Inches Maximum |
| Distance From Loop Center To Tongue End: | 2.006 Inches Nominal |
| Loop Inside Diameter: | 2.610 Inches Minimum And 2.640 Inches Maximum |
| Material: | Rubber Fluorosilicone Class Fq Cushion |
| Material: | Steel Comp 321 Band |
| Material Document And Classification: | Ams 5510 Assn Std Single Material Response Band |
| Material Document And Classification: | Mil-r-25988,ty 2,cl 1,gr 60 Mil Spec Single Material Response Cushion |
| Surface Treatment: | Passivate Band |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Band |
| Style Designator: | Offset Mount |

How to Order

Order this clamp from our inventory online by visiting <u>https://military-fasteners.com/clamps/loop+clamps/MS21919WCJ42</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.