

P/N MS21919WCJ6

Description

diameter: 3/8", loop type, cushioned, corrosion resistant steel with fluorosilicone cushion, MS21919 series clamp

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS21919WCJ6

Minimum Qty (MOQ): 10

NSN: 5340-00-103-2976

Schedule B: 7318.15.2091

ECCN: EAR99

National Motor Freight: 095190, Hardware, Noi









P/N MS21919WCJ6 Specifications

| Tongue Hole Type: | Round, Unthreaded |
|---|---|
| Cushioning Environmental Protection: | Fuel, Aromatic |
| Overall Width: | 0.375 Inches Nominal |
| Diameter: | 0.204 Inches Nominal |
| Material Thickness: | 0.032 Inches Nominal |
| Center To Center Distance Between Loop And Mounting Hole: | 0.592 Inches Nominal |
| Distance From Loop Center To Tongue End: | 0.780 Inches Nominal |
| Loop Inside Diameter: | 0.375 Inches Nominal |
| Material: | Rubber Fluorosilicone Class Fq Cushion |
| Material Document And Classification: | Ams 5510 Assn Std Single Material Response Band |
| Material Document And Classification: | Mil-r-25988 Ty 2 Cl 1 Gr 60 Mil Spec Single Material Response Cushion |
| Surface Treatment: | Passivate Band |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Band |
| Style Designator: | Offset Mount |
| Specification/standard Data: | -81343-as21919 Professional/industrial Association Specification |

How to Order

Order this loop clamp from our inventory online by visiting https://military-fasteners.com/clamps/loop+clamps/MS21919WCJ6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.