

Description

Diameter: 7/16", loop type, cushioned, corrosion resistant steel with fluorosilicone cushion, MS21919 series clamp

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------------|
| SKU / Model: | MS21919WCJ7 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5340-01-161-6234 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |



* See page 2 for technical characteristics

P/N MS21919WCJ7 Specifications

| | |
|--|---|
| Tongue Hole Type: | Round, Unthreaded |
| Cushioning Environmental Protection: | Oil Resistant And Fuel Resistant |
| Overall Width: | 0.365 Inches Minimum And 0.385 Inches Maximum |
| Diameter: | 0.199 Inches Minimum And 0.209 Inches Maximum |
| Material Thickness: | 0.032 Inches Nominal |
| Center To Center Distance Between Loop And Mounting Hole: | 0.608 Inches Minimum And 0.638 Inches Maximum |
| Distance From Loop Center To Tongue End: | 0.811 Inches Nominal |
| Loop Inside Diameter: | 0.423 Inches Minimum And 0.453 Inches Maximum |
| Material: | Rubber Fluorosilicone Class Fq Cushion |
| Material: | Steel Comp 321 Band |
| Material Document And Classification: | Ams 5510 Assn Std Single Material Response Band |
| Material Document And Classification: | Mil-r-25988 Ty 2 Cl 1 Gr 60 Mil Spec Single Material Response Cushion |
| Surface Treatment: | Passivate Band |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Band |
| Style Designator: | Offset Mount |

How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919WCJ7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.