

P/N MS21919WCJ8

Description

diameter: 1/2", loop type, cushioned, corrosion resistant steel with fluorosilicone cushion, MS21919 series clamp

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS21919WCJ8

Minimum Qty (MOQ): 10

NSN: 5340-01-160-0398


ECCN: EAR99

National Motor Freight: 095190, Hardware, Noi Sub 9









^{*} See page 2 for technical characteristics

P/N MS21919WCJ8 Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Oil Resistant And Fuel Resistant
Overall Width:	0.365 Inches Minimum And 0.385 Inches Maximum
Diameter:	0.199 Inches Minimum And 0.209 Inches Maximum
Material Thickness:	0.032 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	0.639 Inches Minimum And 0.669 Inches Maximum
Distance From Loop Center To Tongue End:	0.842 Inches Minimum And 0.902 Inches Maximum
Loop Inside Diameter:	0.485 Inches Minimum And 0.515 Inches Maximum
Special Features:	Cushion Solid Blue
Material:	Rubber Fluorosilicone Class Fq Cushion
Material:	Steel Comp 321 Band
Material Document And Classification:	Mil-r-25988,ty 2,cl 1,gr 60 Mil Spec Single Material Response Cushion
Material Document And Classification:	Mil-s-6721 Mil Spec Single Material Response Band
Surface Treatment:	Passivate Band
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Band
Style Designator:	Offset Mount

How to Order

Order this loop clamp from our inventory online by visiting https://military-fasteners.com/clamps/loop+clamps/MS21919WCJ8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.