

# P/N MS21919WCJ9

## **Description**

diameter: 9/16", loop type, cushioned, corrosion resistant steel with fluorosilicone cushion, MS21919 series clamp

\* Manufacturer certifications are shipped with your order FREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: MS21919WCJ9

Minimum Qty (MOQ): 10

NSN: 5340-00-500-0403

ECCN: EAR99

National Motor Freight: 095190, Hardware, Noi Sub 9









# P/N MS21919WCJ9 Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Fuel, Aromatic And Hydraulic Fluid And Oil Resistant
Overall Width:	0.485 Inches Minimum And 0.515 Inches Maximum
Diameter:	0.204 Inches Nominal
Material Thickness:	0.029 Inches Minimum And 0.036 Inches Maximum
Center To Center Distance Between Loop And Mounting Hole:	0.734 Inches Minimum And 0.764 Inches Maximum
Distance From Loop Center To Tongue End:	0.952 Inches Minimum And 0.982 Inches Maximum
Loop Inside Diameter:	0.548 Inches Minimum And 0.578 Inches Maximum
Material:	Rubber Fluorosilicone Class Fq Cushion Or Rubber Fluorocarbon Class Fpm Cushion
Material:	Steel Comp 321 Band Or Steel Comp 348 Band
Material Document And Classification:	Mil-r-25988 Mil Spec Single Material Response Cushion Or Mil-r-25897 Mil Spec Single Material Response Cushion
Material Document And Classification:	Mil-s-6721 Mil Spec All Material Responses Band
Surface Treatment:	Passivate Band
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Band
Style Designator:	Offset Mount

### **How to Order**

Order this loop clamp from our inventory online by visiting <a href="https://military-fasteners.com/clamps/loop+clamps/MS21919WCJ9">https://military-fasteners.com/clamps/loop+clamps/MS21919WCJ9</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.