

Description

MS21919WDE13 Loop Clamp

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-----------------------|
| SKU / Model: | MS21919WDE13 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5340-01-374-7163 |
| Schedule B: | 7616.10.9090 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi |



* See page 2 for technical characteristics

P/N MS21919WDE13 Specifications

| | |
|--|---|
| Tongue Hole Type: | Round, Threaded |
| Cushioning Environmental Protection: | Ozone Resistant |
| Overall Width: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Material Thickness: | 0.030 Inches Minimum And 0.070 Inches Maximum |
| Center To Center Distance Between Loop And Mounting Hole: | 0.862 Inches Minimum And 0.892 Inches Maximum |
| Distance From Loop Center To Tongue End: | 1.095 Inches Nominal |
| Loop Inside Diameter: | 0.798 Inches Minimum And 0.828 Inches Maximum |
| Special Features: | W" Indicates Wedge Type Cushion,wedge Shall Be Integrally Moled To Cushion Or Vulcanized Using Pressure And Heat To Accomplish A Bond Between Cushion And Wedge |
| Material: | Aluminum Alloy 2024 Bandrubber Ethylene-propylene Class Epm Cushion |
| Material Document And Classification: | Qq-a-250/5 Fed Spec Single Material Response Band |
| Surface Treatment: | Chromate Band |
| Surface Treatment Document And Classification: | Mil-c-5541,cl A Mil Spec Single Treatment Response Band |
| Style Designator: | Offset Mount |

How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919WDE13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.