

P/N MS21919WDE16

Description

Diameter: 13/64", rubber ethylene-propylene class epm cushion

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS21919WDE16
Minimum Qty (MOQ):	10
NSN:	5340-01-224-6921
Schedule B:	7616.10.9090
FCCN:	FAR99



^{*} See page 2 for technical characteristics

P/N MS21919WDE16 Specifications

Tongue Hole Type:	Round, Unthreaded
Overall Width:	0.490 Inches Minimum And 0.510 Inches Maximum
Diameter:	0.199 Inches Minimum And 0.209 Inches Maximum
Material Thickness:	0.050 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	0.955 Inches Minimum And 0.985 Inches Maximum
Distance From Loop Center To Tongue End:	1.188 Inches Nominal
Loop Inside Diameter:	0.985 Inches Minimum And 1.015 Inches Maximum
Material:	Aluminum Alloy 2024 Band
Material:	Rubber Ethylene-propylene Class Epm Cushion
Material Document And Classification:	Qq-a-250/5,temper O Fed Spec Single Material Response Band
Surface Treatment:	Chromate Band
Surface Treatment Document And Classification:	Mil-c-5541,cl 1a Mil Spec Single Treatment Response Band
Style Designator:	Offset Mount

How to Order

Order this loop clamp from our inventory online by visiting https://military-fasteners.com/clamps/loop+clamps/MS21919WDE16 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/loop+clamps/MS21919WDE16 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/loop+clamps/MS21919WDE16 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/loop+clamps/MS21919WDE16 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/ms21919WDE16 and selecting the property of the property of