

P/N MS21919WDE44

Description

Diameter: 13/64", plastic tetrafluoroethylene cushion

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

| SKU / Model: | MS21919WDE44 |
|--------------------|------------------|
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5340-01-291-0825 |
| Schedule B: | 7616.10.9090 |
| ECCN: | 9A991 |



^{*} See page 2 for technical characteristics

P/N MS21919WDE44 Specifications

| Tongue Hole Type: | Round, Unthreaded |
|---|--|
| Cushioning Environmental Protection: | Flame Resistant |
| Overall Width: | 0.485 Inches Minimum And 0.515 Inches Maximum |
| Diameter: | 0.204 Inches Nominal |
| Material Thickness: | 0.058 Inches Minimum And 0.068 Inches Maximum |
| Center To Center Distance Between Loop And Mounting Hole: | 1.860 Inches Minimum And 1.890 Inches Maximum |
| Distance From Loop Center To Tongue End: | 2.078 Inches Minimum And 2.118 Inches Maximum |
| Loop Inside Diameter: | 2.735 Inches Minimum And 2.765 Inches Maximum |
| Application/function: | M196.0 To P260.0 Deg C Temp Appl |
| Material: | Aluminum Alloy 2024 Band |
| Material: | Plastic Tetrafluoroethylene Cushion |
| Material Document And Classification: | L-p-403,type 1,class 1 Fed Spec Single Material Response Cushion |
| Material Document And Classification: | Qq-a0250/5,t0,a92024 Fed Spec Single Material Response Band |
| Style Designator: | Offset Mount |
| Supplementary Features: | White Cushion W/ Red Stripe |
| Specification/standard Data: | 96906-ms21122 Government Standard |

How to Order

Order this clamp from our inventory online by visiting https://military-fasteners.com/clamps/loop+clamps/MS21919WDE44 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.