

Description

Diameter: 13/64", plastic tetrafluoroethylene cushion

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21919WDE44
Minimum Qty (MOQ):	5 EA
NSN:	5340-01-291-0825
Schedule B:	7616.10.9090
ECCN:	9A991

NO IMAGE
AVAILABLE

P/N MS21919WDE44 Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Flame Resistant
Overall Width:	0.485 Inches Minimum And 0.515 Inches Maximum
Diameter:	0.204 Inches Nominal
Material Thickness:	0.058 Inches Minimum And 0.068 Inches Maximum
Center To Center Distance Between Loop And Mounting Hole:	1.860 Inches Minimum And 1.890 Inches Maximum
Distance From Loop Center To Tongue End:	2.078 Inches Minimum And 2.118 Inches Maximum
Loop Inside Diameter:	2.735 Inches Minimum And 2.765 Inches Maximum
Application/function:	M196.0 To P260.0 Deg C Temp Appl
Material:	Aluminum Alloy 2024 Band
Material:	Plastic Tetrafluoroethylene Cushion
Material Document And Classification:	L-p-403,type 1,class 1 Fed Spec Single Material Response Cushion
Material Document And Classification:	Qq-a0250/5,t0,a92024 Fed Spec Single Material Response Band
Style Designator:	Offset Mount
Supplementary Features:	White Cushion W/ Red Stripe
Specification/standard Data:	96906-ms21122 Government Standard

How to Order

Order this clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919WDE44> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.