

Description

Diameter: 13/64", rubber ethylene-propylene class epm cushion

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|------------------------------------|
| SKU / Model: | MS21919WDE5 |
| Minimum Qty (MOQ): | 20 EA |
| NSN: | 5340-01-219-3657 |
| Schedule B: | 7616.10.9090 |
| ECCN: | 9A991 |
| National Motor Freight: | 013120, Aluminum Article Noi Sub 6 |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS21919WDE5 Specifications

| | |
|--|---|
| Tongue Hole Type: | Round, Unthreaded |
| Cushioning Environmental Protection: | Ozone Resistant And Fuel Resistant |
| Overall Width: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Diameter: | 0.199 Inches Minimum And 0.209 Inches Maximum |
| Material Thickness: | 0.032 Inches Nominal |
| Center To Center Distance Between Loop And Mounting Hole: | 0.747 Inches Minimum And 0.777 Inches Maximum |
| Distance From Loop Center To Tongue End: | 0.950 Inches Minimum And 1.010 Inches Maximum |
| Loop Inside Diameter: | 0.298 Inches Minimum And 0.328 Inches Maximum |
| Material: | Aluminum Alloy 1230 Band |
| Material: | Rubber Ethylene-propylene Class Epm Cushion |
| Material Document And Classification: | Qq-a-250/5 Fed Spec Single Material Response Band |
| Style Designator: | Offset Mount |

How to Order

Order this clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919WDE5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.