

Description

Diameter: 13/64", rubber butadiene-acrylonitrile cushion, MS21919 series clamp

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|------------------------------------|
| SKU / Model: | MS21919WDF20 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5340-01-217-0921 |
| Schedule B: | 7616.10.9090 |
| ECCN: | EAR99 |
| National Motor Freight: | 013120, Aluminum Article Noi Sub 6 |



* See page 2 for technical characteristics

P/N MS21919WDF20 Specifications

| | |
|--|---|
| Tongue Hole Type: | Round, Unthreaded |
| Overall Width: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Diameter: | 0.199 Inches Minimum And 0.209 Inches Maximum |
| Material Thickness: | 0.062 Inches Nominal |
| Center To Center Distance Between Loop And Mounting Hole: | 1.109 Inches Minimum And 1.139 Inches Maximum |
| Distance From Loop Center To Tongue End: | 1.342 Inches Nominal |
| Loop Inside Diameter: | 1.235 Inches Minimum And 1.265 Inches Maximum |
| Material: | Aluminum Alloy 2024 Band |
| Material: | Rubber Butadiene-acrylonitrile Class Nbr Cushion |
| Material Document And Classification: | Ams 3215 Assn Std Single Material Response Cushion |
| Material Document And Classification: | Qq-a-250/5 O Fed Spec Single Material Response Band |
| Surface Treatment: | Chromate Band |
| Surface Treatment Document And Classification: | Mil-c-5541 Mil Spec Single Treatment Response Band |
| Style Designator: | Offset Mount |

How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919WDF20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.