

Description

Diameter: 13/64", rubber butadiene-acrylonitrile class cushion

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21919WDF25
Minimum Qty (MOQ):	10
NSN:	5340-01-168-9783
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	013120, Aluminum Article Noi Sub 6



P/N MS21919WDF25 Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Fuel Resistant And Ozone Resistant
Overall Width:	0.500 Inches Nominal
Diameter:	0.204 Inches Nominal
Material Thickness:	0.058 Inches Minimum And 0.068 Inches Maximum
Center To Center Distance Between Loop And Mounting Hole:	1.281 Inches Nominal
Distance From Loop Center To Tongue End:	1.499 Inches Nominal
Loop Inside Diameter:	1.548 Inches Minimum And 1.578 Inches Maximum
Material:	Rubber Butadiene-acrylonitrile Class Nbr Cushion
Material Document And Classification:	Ams 3215 Assn Std Single Material Response Cushion
Material Document And Classification:	Qq-a-250/5 Fed Spec Single Material Response Band
Surface Treatment:	Chromate Band
Surface Treatment Document And Classification:	Mil-c-5541 Cl 1a Mil Spec Single Treatment Response Band
Style Designator:	Offset Mount

How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919WDF25> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.