

Description

Diameter: 1/4", loop type, cushioned, aluminum with nitrile cushion, MS21919 series clamp

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[MS21919DF4](#)

SKU / Model:	MS21919WDF4
Minimum Qty (MOQ):	10
NSN:	5340-00-286-9420
Schedule B:	7616.99.5190
ECCN:	EAR99
National Motor Freight:	013120, Aluminum Article Noi Sub 6



* See page 2 for technical characteristics

P/N MS21919WDF4 Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Fuel Resistant
Overall Width:	0.490 Inches Minimum And 0.510 Inches Maximum
Diameter:	0.204 Inches Nominal
Material Thickness:	0.032 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	0.514 Inches Minimum And 0.544 Inches Maximum
Distance From Loop Center To Tongue End:	0.747 Inches Nominal
Loop Inside Diameter:	0.235 Inches Minimum And 0.265 Inches Maximum
Special Features:	Wedge Type Cushion Construction
Material:	Rubber Butadiene-acrylonitrile Class Nbr Cushion
Material Document And Classification:	Ams 3215 Assn Std Single Material Response Cushion
Material Document And Classification:	Qq-a-250/5 Fed Spec Single Material Response Band
Surface Treatment:	Chromate Band
Surface Treatment Document And Classification:	-1l-c-5541 Mil Spec Single Treatment Response Band
Style Designator:	Offset Mount

How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919WDF4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.