

Description

Diameter: 1/4", loop type, cushioned, aluminum with nitrile cushion, MS21919 series clamp

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[MS21919DF4](#)

| | |
|-------------------------|------------------------------------|
| SKU / Model: | MS21919WDF4 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5340-00-286-9420 |
| Schedule B: | 7616.99.5190 |
| ECCN: | EAR99 |
| National Motor Freight: | 013120, Aluminum Article Noi Sub 6 |



* See page 2 for technical characteristics

P/N MS21919WDF4 Specifications

| | |
|--|--|
| Tongue Hole Type: | Round, Unthreaded |
| Cushioning Environmental Protection: | Fuel Resistant |
| Overall Width: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Diameter: | 0.204 Inches Nominal |
| Material Thickness: | 0.032 Inches Nominal |
| Center To Center Distance Between Loop And Mounting Hole: | 0.514 Inches Minimum And 0.544 Inches Maximum |
| Distance From Loop Center To Tongue End: | 0.747 Inches Nominal |
| Loop Inside Diameter: | 0.235 Inches Minimum And 0.265 Inches Maximum |
| Special Features: | Wedge Type Cushion Construction |
| Material: | Rubber Butadiene-acrylonitrile Class Nbr Cushion |
| Material Document And Classification: | Ams 3215 Assn Std Single Material Response Cushion |
| Material Document And Classification: | Qq-a-250/5 Fed Spec Single Material Response Band |
| Surface Treatment: | Chromate Band |
| Surface Treatment Document And Classification: | -1I-c-5541 Mil Spec Single Treatment Response Band |
| Style Designator: | Offset Mount |

How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919WDF4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.