

Description

Diameter: 3/4", cushioned, aluminum with chloroprene cushion, MS21919 series clamp

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[MS21919DG12](#)

SKU / Model:	MS21919WDG12
Minimum Qty (MOQ):	20
NSN:	5340-00-286-9427
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	013120, Aluminum Article Noi Sub 6



* See page 2 for technical characteristics

P/N MS21919WDG12 Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Weather Resistant
Overall Width:	0.490 Inches Minimum And 0.510 Inches Maximum
Diameter:	0.204 Inches Nominal
Material Thickness:	0.050 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	0.830 Inches Minimum And 0.860 Inches Maximum
Distance From Loop Center To Tongue End:	1.063 Inches Nominal
Loop Inside Diameter:	0.735 Inches Minimum And 0.765 Inches Maximum
Material:	Rubber Chloroprene Class Cr Cushion
Material Document And Classification:	Ams 3209 Assn Std Single Material Response Cushion
Material Document And Classification:	Qq-a-250/5 Fed Spec Single Material Response Band
Surface Treatment:	Chromate Band
Surface Treatment Document And Classification:	-1I-c-5541 Mil Spec Single Treatment Response Band
Style Designator:	Offset Mount
Nondefinitive Spec/std Data:	4 Type And A Class

How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919WDG12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.