

P/N MS21919WDG16

Description

Diameter: 1", cushioned, aluminum with chloroprene cushion, MS21919 series clamp

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

MS21919DG16

SKU / Model: MS21919WDG16

Minimum Qty (MOQ): 10

NSN: 5340-00-286-9418

Schedule B: 7616.10.9090

ECCN: EAR99

National Motor Freight: 013120, Aluminum Article Noi Sub 6









P/N MS21919WDG16 Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Weather Resistant
Overall Width:	0.490 Inches Minimum And 0.510 Inches Maximum
Diameter:	0.204 Inches Nominal
Material Thickness:	0.050 Inches Nominal
End Item Identification:	Mrap-rg-33 Armored Utility Vehicle (auv)
Center To Center Distance Between Loop And Mounting Hole:	0.955 Inches Minimum And 0.985 Inches Maximum
Distance From Loop Center To Tongue End:	1.188 Inches Nominal
Loop Inside Diameter:	0.985 Inches Minimum And 1.015 Inches Maximum
Material:	Aluminum Alloy 2024 Band
Material:	Rubber Chloroprene Class Cr Cushion
Material Document And Classification:	Ams 3209 Assn Std Single Material Response Cushion
Material Document And Classification:	Qq-a-250/5 Fed Spec Single Material Response Band
Surface Treatment:	Chromate Band
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Cushion
Style Designator:	Offset Mount

How to Order

Order this loop clamp from our inventory online by visiting https://military-fasteners.com/clamps/loop+clamps/MS21919WDG16 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.