

P/N MS21919WDG17

Description

Diameter: 1-1/16", cushioned, aluminum with chloroprene cushion, MS21919 series clamp

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

AS21919WDG17

SKU / Model: MS21919WDG17

Minimum Qty (MOQ): 20

NSN: 5340-00-200-7451

Schedule B: 7616.10.9090

ECCN: EAR99

National Motor Freight: 013120, Aluminum Article Noi Sub 6









P/N MS21919WDG17 Specifications

Tongue Hole Type:	Round, Unthreaded
Overall Width:	0.500 Inches Nominal
Diameter:	0.204 Inches Nominal
Material Thickness:	0.037 Inches Minimum And 0.043 Inches Maximum
End Item Identification:	Rg-31 Mrap &rcv
Center To Center Distance Between Loop And Mounting Hole:	0.928 Inches Nominal
Distance From Loop Center To Tongue End:	1.146 Inches Nominal
Loop Inside Diameter:	1.048 Inches Minimum And 1.078 Inches Maximum
Special Features:	Wedge Type Cushion Construction
Material:	Aluminum Alloy 2024 Band
Material:	Rubber Cushion
Material Document And Classification:	Qq-a-250/5 Fed Spec Single Material Response Band
Style Designator:	Offset Mount
Nondefinitive Spec/std Data:	4 Type And A Class
Departure From Cited Designator:	As Differentiated By Special Features

How to Order

Order this loop clamp from our inventory online by visiting https://military-fasteners.com/clamps/loop+clamps/MS21919WDG17 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/loop+clamps/MS21919WDG17 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/loop+clamps/MS21919WDG17 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/ms21919WDG17 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/ms21919WDG17 and selecting the property of the property