

Description

diameter: 1-3/8", cushioned, aluminum band, chloroprene cushion

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[AS21919WDG22](#)

| | |
|-------------------------|------------------------------------|
| SKU / Model: | MS21919WDG22 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5340-00-664-8165 |
| ECCN: | EAR99 |
| National Motor Freight: | 013120, Aluminum Article Noi Sub 6 |



* See page 2 for technical characteristics

P/N MS21919WDG22 Specifications

| | |
|--|--|
| Tongue Hole Type: | Round, Unthreaded |
| Cushioning Environmental Protection: | Weather Resistant |
| Overall Width: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Diameter: | 0.204 Inches Nominal |
| Material Thickness: | 0.062 Inches Nominal |
| Center To Center Distance Between Loop And Mounting Hole: | 1.172 Inches Minimum And 1.202 Inches Maximum |
| Distance From Loop Center To Tongue End: | 1.405 Inches Nominal |
| Loop Inside Diameter: | 1.360 Inches Minimum And 1.390 Inches Maximum |
| Material: | Aluminum Alloy 2024 Band |
| Material: | Rubber Chloroprene Class Cr Cushion |
| Material Document And Classification: | Ams 3209 Assn Std Single Material Response Cushion |
| Material Document And Classification: | Qq-a-250/5 Fed Spec Single Material Response Band |
| Surface Treatment: | Chromate Band |
| Surface Treatment Document And Classification: | Mil-c-5541 Mil Spec Single Treatment Response Band |
| Style Designator: | Offset Mount |
| Specification/standard Data: | 26512-gs14 Manufacturers Specification |

How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919WDG22> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.