

Description

Diameter: 1-3/4", cushioned, aluminum with chloroprene cushion, MS21919 series clamp

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[AS21919WDG28](#)

SKU / Model:	MS21919WDG28
Minimum Qty (MOQ):	10
NSN:	5340-00-598-0529
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



* See page 2 for technical characteristics

P/N MS21919WDG28 Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Weather Resistant
Overall Width:	0.490 Inches Minimum And 0.510 Inches Maximum
Diameter:	0.204 Inches Nominal
Material Thickness:	0.062 Inches Nominal
End Item Identification:	Mrap Rg-33 Auv
Center To Center Distance Between Loop And Mounting Hole:	1.359 Inches Minimum And 1.389 Inches Maximum
Distance From Loop Center To Tongue End:	1.592 Inches Nominal
Loop Inside Diameter:	1.735 Inches Minimum And 1.765 Inches Maximum
Material:	Rubber Chloroprene Class Cr Cushion
Material Document And Classification:	Ams 3209 Assn Std Single Material Response Cushion
Material Document And Classification:	Qq-a-250/5 Fed Spec Single Material Response Band
Surface Treatment:	Chromate Band
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Band
Style Designator:	Offset Mount

How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919WDG28> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.