

Description

diameter: 2-1/8", cushioned, aluminum with chloroprene cushion

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[AS21919WDG34](#)

SKU / Model:	MS21919WDG34
Minimum Qty (MOQ):	10
NSN:	5340-00-582-7354
ECCN:	EAR99
National Motor Freight:	013120, Aluminum Article Noi Sub 6



* See page 2 for technical characteristics

P/N MS21919WDG34 Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Weather Resistant
Overall Width:	0.490 Inches Minimum And 0.510 Inches Maximum
Diameter:	0.204 Inches Nominal
Material Thickness:	0.063 Inches Nominal
Material Diameter:	0.062 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	1.547 Inches Minimum And 1.577 Inches Maximum
Distance From Loop Center To Tongue End:	1.780 Inches Nominal
Loop Inside Diameter:	2.110 Inches Minimum And 2.140 Inches Maximum
Material:	Aluminum Alloy 2024 Band
Material:	Rubber Chloroprene Class Cr Cushion
Material Document And Classification:	Ams 3209 Assn Std Single Material Response Cushion
Material Document And Classification:	Qq-a-250/5 Fed Spec Single Material Response Band
Surface Treatment:	Chromate Band
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Band
Style Designator:	Offset Mount

How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919WDG34> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.