

Description

2-3/16" diameter, cushioned, aluminum with chloroprene cushion

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|------------------------------------|
| SKU / Model: | MS21919WDG35 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5340-00-515-0597 |
| ECCN: | EAR99 |
| National Motor Freight: | 013120, Aluminum Article Noi Sub 6 |



* See page 2 for technical characteristics

P/N MS21919WDG35 Specifications

| | |
|--|--|
| Tongue Hole Type: | Round, Unthreaded |
| Cushioning Environmental Protection: | Weather Resistant |
| Overall Width: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Diameter: | 0.204 Inches Nominal |
| Material Thickness: | 0.062 Inches Nominal |
| Center To Center Distance Between Loop And Mounting Hole: | 1.579 Inches Minimum And 1.609 Inches Maximum |
| Distance From Loop Center To Tongue End: | 1.812 Inches Nominal |
| Loop Inside Diameter: | 2.173 Inches Minimum And 2.203 Inches Maximum |
| Material: | Rubber Chloroprene Class Cr Cushion |
| Material Document And Classification: | Ams 3209 Assn Std Single Material Response Cushion |
| Surface Treatment: | Chromate Band |
| Surface Treatment Document And Classification: | -1I-c-5541 Mil Spec Single Treatment Response Band |
| Style Designator: | Offset Mount |
| Nondefinitive Spec/std Data: | 4 Type And A Class |

How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919WDG35> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.