

# P/N MS21919WDG37

Military-Fasteners.com

#### Description

diameter: 2-5/16", cushioned, aluminum with chloroprene cushion, MS21919 series clamp

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	MS21919WDG37
Minimum Qty (MOQ):	5
NSN:	5340-00-685-0508
ECCN:	EAR99
National Motor Freight:	013120, Aluminum Article Noi Sub 6



## P/N MS21919WDG37 Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Weather Resistant
Overall Width:	0.490 Inches Minimum And 0.510 Inches Maximum
Diameter:	0.204 Inches Nominal
Material Thickness:	0.062 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	1.640 Inches Minimum And 1.670 Inches Maximum
Distance From Loop Center To Tongue End:	1.873 Inches Nominal
Loop Inside Diameter:	2.297 Inches Minimum And 2.327 Inches Maximum
Material:	Rubber Chloroprene Class Cr Cushion
Material Document And Classification:	Ams 3209 Assn Std Single Material Response Cushion
Surface Treatment:	Chromate Band
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Band
Style Designator:	Offset Mount

### How to Order

Order this loop clamp from our inventory online by visiting <u>https://military-fasteners.com/clamps/loop+clamps/MS21919WDG37</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.