

P/N MS21919WDH10

Military-Fasteners.com

Description

Diameter: 13/64", steel comp 321 band

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS21919WDH10
Minimum Qty (MOQ):	5 EA
NSN:	5340-01-140-4629
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9



P/N MS21919WDH10 Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Corrosion Resistant And Weather Resistant And Oil Resistant
Overall Width:	0.490 Inches Minimum And 0.510 Inches Maximum
Diameter:	0.199 Inches Minimum And 0.209 Inches Maximum
Material Thickness:	0.032 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	0.765 Inches Minimum And 0.795 Inches Maximum
Distance From Loop Center To Tongue End:	0.998 Inches Nominal
Loop Inside Diameter:	0.610 Inches Minimum And 0.640 Inches Maximum
Material:	Rubber Silicone Class Q Cushion
Material:	Steel Comp 321 Band
Material Document And Classification:	Ams 3303 Assn Std Single Material Response Cushion
Material Document And Classification:	Mil-s-6721 Mil Spec Single Material Response Band
Surface Treatment:	Passivate Band
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Band
Style Designator:	Offset Mount

How to Order

Order this clamp from our inventory online by visiting <u>https://military-fasteners.com/clamps/loop+clamps/MS21919WDH10</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.