

Description

Diameter: 13/64", steel comp 1010 bandrubber butadiene-acrylonitrile class nbr cushion

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21919WF12
Minimum Qty (MOQ):	5
NSN:	5340-01-375-3012
National Motor Freight:	095190, Hardware, Noi



* See page 2 for technical characteristics

P/N MS21919WF12 Specifications

Tongue Hole Type:	Round, Unthreaded
Overall Width:	0.490 Inches Minimum And 0.510 Inches Maximum
Diameter:	0.199 Inches Minimum And 0.209 Inches Maximum
Material Thickness:	0.032 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	0.827 Inches Minimum And 0.857 Inches Maximum
Distance From Loop Center To Tongue End:	1.060 Inches Nominal
Loop Inside Diameter:	0.735 Inches Minimum And 0.765 Inches Maximum
Material:	Steel Comp 1010 Bandrubber Butadiene-acrylonitrile Class Nbr Cushion
Material Document And Classification:	Astm A109 Assn Std Single Material Response Bandams 3215 Assn Std Single Material Response Cushion
Surface Treatment:	Cadmium Band
Surface Treatment Document And Classification:	Qq-p-416 Ty 1 Cl 2 Fed Spec Single Treatment Response Band
Style Designator:	Offset Mount

How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919WF12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.