

Description

Diameter: 13/64", steel comp 1010 bandrubber butadiene-acrylonitrile class nbr cushion

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------|
| SKU / Model: | MS21919WF12 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5340-01-375-3012 |
| National Motor Freight: | 095190, Hardware, Noi |

NO IMAGE
AVAILABLE

P/N MS21919WF12 Specifications

| | |
|--|--|
| Tongue Hole Type: | Round, Unthreaded |
| Overall Width: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Diameter: | 0.199 Inches Minimum And 0.209 Inches Maximum |
| Material Thickness: | 0.032 Inches Nominal |
| Center To Center Distance Between Loop And Mounting Hole: | 0.827 Inches Minimum And 0.857 Inches Maximum |
| Distance From Loop Center To Tongue End: | 1.060 Inches Nominal |
| Loop Inside Diameter: | 0.735 Inches Minimum And 0.765 Inches Maximum |
| Material: | Steel Comp 1010 Bandrubber Butadiene-acrylonitrile Class Nbr Cushion |
| Material Document And Classification: | Astm A109 Assn Std Single Material Response Bandams 3215 Assn Std Single Material Response Cushion |
| Surface Treatment: | Cadmium Band |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 1 Cl 2 Fed Spec Single Treatment Response Band |
| Style Designator: | Offset Mount |

How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919WF12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.