

**Description**

Diameter: 13/64", steel comp 1010 bandrubber butadiene-acrylonitrile class nbr cushion

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS21919WF12
Minimum Qty (MOQ):	5
NSN:	5340-01-375-3012
National Motor Freight:	095190, Hardware, Noi



\* See page 2 for technical characteristics

## P/N MS21919WF12 Specifications

<b>Tongue Hole Type:</b>	Round, Unthreaded
<b>Overall Width:</b>	0.490 Inches Minimum And 0.510 Inches Maximum
<b>Diameter:</b>	0.199 Inches Minimum And 0.209 Inches Maximum
<b>Material Thickness:</b>	0.032 Inches Nominal
<b>Center To Center Distance Between Loop And Mounting Hole:</b>	0.827 Inches Minimum And 0.857 Inches Maximum
<b>Distance From Loop Center To Tongue End:</b>	1.060 Inches Nominal
<b>Loop Inside Diameter:</b>	0.735 Inches Minimum And 0.765 Inches Maximum
<b>Material:</b>	Steel Comp 1010 Bandrubber Butadiene-acrylonitrile Class Nbr Cushion
<b>Material Document And Classification:</b>	Astm A109 Assn Std Single Material Response Bandams 3215 Assn Std Single Material Response Cushion
<b>Surface Treatment:</b>	Cadmium Band
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 1 Cl 2 Fed Spec Single Treatment Response Band
<b>Style Designator:</b>	Offset Mount

## How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919WF12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.