

Description

Diameter: 13/64", steel comp 1008 band or steel comp 1009 band or steel comp 1015 band or steel comp 1018 band or steel comp 1020 band

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21919WF19
Minimum Qty (MOQ):	10 EA
NSN:	5340-01-157-0955
Schedule B:	7318.29.0000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



* See page 2 for technical characteristics

P/N MS21919WF19 Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Fuel Resistant
Overall Width:	0.490 Inches Minimum And 0.510 Inches Maximum
Diameter:	0.199 Inches Minimum And 0.209 Inches Maximum
Material Thickness:	0.032 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	1.046 Inches Minimum And 1.076 Inches Maximum
Distance From Loop Center To Tongue End:	1.279 Inches Nominal
Loop Inside Diameter:	1.173 Inches Minimum And 1.203 Inches Maximum
Material:	Rubber Butadiene-acrylonitrile Class Nbr Cushion
Material:	Steel Comp 1008 Band Or Steel Comp 1009 Band Or Steel Comp 1015 Band Or Steel Comp 1018 Band Or Steel Comp 1020 Band
Material Document And Classification:	Ams 3215 Assn Std Single Material Response Cushion
Surface Treatment:	Cadmium Band
Surface Treatment Document And Classification:	Qq-p-416 Type 1 Class 2 Fed Spec Single Treatment Response Band
Style Designator:	Offset Mount

How to Order

Order this clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919WF19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.