

Description

Diameter: 13/64", steel comp 1008 band or steel comp 1009 band or steel comp 1015 band or steel comp 1018 band or steel comp 1020 band

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------|
| SKU / Model: | MS21919WF19 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5340-01-157-0955 |
| Schedule B: | 7318.29.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi |

NO IMAGE
AVAILABLE

P/N MS21919WF19 Specifications

| | |
|--|--|
| Tongue Hole Type: | Round, Unthreaded |
| Cushioning Environmental Protection: | Fuel Resistant |
| Overall Width: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Diameter: | 0.199 Inches Minimum And 0.209 Inches Maximum |
| Material Thickness: | 0.032 Inches Nominal |
| Center To Center Distance Between Loop And Mounting Hole: | 1.046 Inches Minimum And 1.076 Inches Maximum |
| Distance From Loop Center To Tongue End: | 1.279 Inches Nominal |
| Loop Inside Diameter: | 1.173 Inches Minimum And 1.203 Inches Maximum |
| Material: | Rubber Butadiene-acrylonitrile Class Nbr Cushion |
| Material: | Steel Comp 1008 Band Or Steel Comp 1009 Band Or Steel Comp 1015 Band Or Steel Comp 1018 Band Or Steel Comp 1020 Band |
| Material Document And Classification: | Ams 3215 Assn Std Single Material Response Cushion |
| Surface Treatment: | Cadmium Band |
| Surface Treatment Document And Classification: | Qq-p-416 Type 1 Class 2 Fed Spec Single Treatment Response Band |
| Style Designator: | Offset Mount |

How to Order

Order this clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919WF19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.