

Description

Diameter: 13/64", steel comp band, MS21919 series clamp

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------|
| SKU / Model: | MS21919WG18 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5340-00-579-6364 |
| Schedule B: | 7318.29.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi |



* See page 2 for technical characteristics

P/N MS21919WG18 Specifications

| | |
|--|--|
| Tongue Hole Type: | Round, Unthreaded |
| Cushioning Environmental Protection: | Weather Resistant |
| Overall Width: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Diameter: | 0.204 Inches Nominal |
| Material Thickness: | 0.032 Inches Nominal |
| Center To Center Distance Between Loop And Mounting Hole: | 1.015 Inches Minimum And 1.045 Inches Maximum |
| Distance From Loop Center To Tongue End: | 1.248 Inches Nominal |
| Loop Inside Diameter: | 1.110 Inches Minimum And 1.140 Inches Maximum |
| Material: | Rubber Chloroprene Class Cr Cushion |
| Material: | Steel Comp 1008 Band Or Steel Comp 1009 Band Or Steel Comp 1015 Band Or Steel Comp 1018 Band Or Steel Comp 1020 Band |
| Material Document And Classification: | Ams 3209 Assn Std Single Material Response Cushion |
| Surface Treatment: | Cadmium Band |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 1 Cl 2 Fed Spec Single Treatment Response Band |
| Style Designator: | Offset Mount |
| Nondefinitive Spec/std Data: | 4 Type And B Class |

How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919WG18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.