

**Description**

Diameter: 13/64", steel comp 1008 band or steel comp 1009 band or steel comp 1015 band or steel comp 1018 band or steel comp 1020 band

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS21919WG19
Minimum Qty (MOQ):	5 EA
NSN:	5340-00-818-7358
Schedule B:	7318.29.0000
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS21919WG19 Specifications

<b>Tongue Hole Type:</b>	Round, Unthreaded
<b>Cushioning Environmental Protection:</b>	Weather Resistant
<b>Overall Width:</b>	0.490 Inches Minimum And 0.510 Inches Maximum
<b>Diameter:</b>	0.204 Inches Nominal
<b>Material Thickness:</b>	0.032 Inches Nominal
<b>Center To Center Distance Between Loop And Mounting Hole:</b>	1.046 Inches Minimum And 1.076 Inches Maximum
<b>Distance From Loop Center To Tongue End:</b>	1.279 Inches Nominal
<b>Loop Inside Diameter:</b>	1.173 Inches Minimum And 1.203 Inches Maximum
<b>Material:</b>	Rubber Chloroprene Class Cr Cushion
<b>Material:</b>	Steel Comp 1008 Band Or Steel Comp 1009 Band Or Steel Comp 1015 Band Or Steel Comp 1018 Band Or Steel Comp 1020 Band
<b>Material Document And Classification:</b>	Ams 3209 Assn Std Single Material Response Cushion
<b>Surface Treatment:</b>	Cadmium Band
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 1 Cl 2 Fed Spec Single Treatment Response Band
<b>Style Designator:</b>	Offset Mount

## How to Order

Order this clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919WG19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.