

P/N MS21919WG22

Description

Diameter: 13/64", rubber chloroprene class cr cushion

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

National Motor Freight:

| SKU / Model: | MS21919WG22 |
|--------------------|------------------|
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5340-00-677-0565 |
| Schedule B: | 7318.29.0000 |
| ECCN: | 9A991 |

095190, Hardware, Noi Sub 9



^{*} See page 2 for technical characteristics

P/N MS21919WG22 Specifications

| Tongue Hole Type: | Round, Unthreaded |
|---|--|
| Cushioning Environmental Protection: | Weather Resistant |
| Overall Width: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Diameter: | 0.204 Inches Nominal |
| Material Thickness: | 0.032 Inches Nominal |
| Center To Center Distance Between Loop And Mounting Hole: | 1.140 Inches Minimum And 1.170 Inches Maximum |
| Distance From Loop Center To Tongue End: | 1.373 Inches Nominal |
| Loop Inside Diameter: | 1.360 Inches Minimum And 1.390 Inches Maximum |
| Material: | Rubber Chloroprene Class Cr Cushion |
| Material Document And Classification: | Ams 3209 Assn Std Single Material Response Cushion |
| Surface Treatment: | Cadmium Band |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 1 Cl 2 Fed Spec Single Treatment Response Band |
| Style Designator: | Offset Mount |

How to Order

Order this clamp from our inventory online by visiting https://military-fasteners.com/clamps/loop+clamps/MS21919WG22 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/loop+clamps/MS21919WG22 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/loop+clamps/MS21919WG22 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/loop+clamps/mS21919WG22 and selecting the quantity you want then