

P/N MS21919WG24

Military-Fasteners.com

Description

Diameter: 13/64", steel comp 1008 band or steel comp 1009 band or steel comp 1015 band or steel comp 1018 band or steel comp 1020 band

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

| SKU / Model: | MS21919WG24 |
|-------------------------|-----------------------------|
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5340-00-291-5337 |
| Schedule B: | 7318.29.0000 |
| ECCN: | 9A991 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |



P/N MS21919WG24 Specifications

| Tongue Hole Type: | Round, Unthreaded |
|--|---|
| Cushioning Environmental Protection: | Weather Resistant |
| Overall Width: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Diameter: | 0.204 Inches Nominal |
| Material Thickness: | 0.032 Inches Nominal |
| Center To Center Distance Between Loop And Mounting Hole: | 1.202 Inches Minimum And 1.232 Inches Maximum |
| Distance From Loop Center To Tongue End: | 1.435 Inches Nominal |
| Loop Inside Diameter: | 1.485 Inches Minimum And 1.515 Inches Maximum |
| Special Features: | Wedge Type Cushion Construction |
| Material: | Rubber Chloroprene Class Cr Cushion |
| Material: | Steel Comp 1008 Band Or Steel Comp 1009 Band Or Steel Comp 1015 Band Or Steel Comp 1018 Band Or Steel Comp 1020 Band |
| Material Document And Classification: | Ams 3209 Assn Std Single Material Response Cushion |
| Surface Treatment: | Cadmium Band |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 1 Cl 2 Fed Spec Single Treatment Response Band |
| Style Designator: | Offset Mount |
| Departure From Cited Designator: | As Modified By Special Features |

How to Order

Order this clamp from our inventory online by visiting <u>https://military-fasteners.com/clamps/loop+clamps/MS21919WG24</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.