

P/N MS21919WH13

Description

13/16" diameter - loop type clamp - cushioned - 400°,, steel with silicone cushion

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21919WH13
Minimum Qty (MOQ):	10
NSN:	5340-00-817-5328
National Motor Freight:	095190, Hardware, Noi Sub 9



^{*} See page 2 for technical characteristics

P/N MS21919WH13 Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Heat
Overall Width:	0.500 Inches Nominal
Diameter:	0.204 Inches Nominal
Material Thickness:	0.030 Inches Minimum And 0.035 Inches Maximum
Center To Center Distance Between Loop And Mounting Hole:	0.858 Inches Nominal
Distance From Loop Center To Tongue End:	1.076 Inches Nominal
Loop Inside Diameter:	0.798 Inches Minimum And 0.828 Inches Maximum
Material:	Rubber Synthetic Cushion
Material:	Steel Comp 1017 Band
Material Document And Classification:	Qq-s-636,cond 4 Fed Spec Single Material Response Band
Surface Treatment:	Cadmium Band
Style Designator:	Offset Mount

How to Order

Order this loop clamp from our inventory online by visiting https://military-fasteners.com/clamps/loop+clamps/MS21919WH13 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/loop+clamps/MS21919WH13 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/loop+clamps/MS21919WH13 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/ms21919WH13 and selecting the quantity you want https://military-fasteners.com/clamps/ms21919WH13 and selecting the your cart you can check out https://military-fasteners.com/clamps/ms21919WH13 and selecting the your cart you can check out https://military-fasteners.com/clamps/ms21919WH13 and selecting the your cart your cart you can check you can ch