

P/N MS21919WH14

Description

7/8" diameter - loop type clamp - cushioned - 400°,, steel with silicone cushion"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21919WH14
Minimum Qty (MOQ):	10
NSN:	5340-00-811-2618
National Motor Freight:	095190, Hardware, Noi Sub 9



P/N MS21919WH14 Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Heat
Overall Width:	0.500 Inches Nominal
Diameter:	0.204 Inches Nominal
Material Thickness:	0.032 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	0.889 Inches Nominal
Distance From Loop Center To Tongue End:	1.107 Inches Nominal
Loop Inside Diameter:	0.875 Inches Nominal
Special Features:	Requires Environmental Test In Accordance W/special Projects Fbm Plan Op2747
Material:	Rubber Cushion
Material:	Steel Band
Material Document And Classification:	Qq-a-s-640,cond 4 Fed Spec Single Material Response Band
Surface Treatment:	Cadmium Band
Style Designator:	Offset Mount
Departure From Cited Designator:	As Modifeied By Special Features

How to Order

Order this loop clamp from our inventory online by visiting https://military-fasteners.com/clamps/loop+clamps/MS21919WH14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/loop+clamps/MS21919WH14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/loop+clamps/MS21919WH14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/ms21919WH14 and selecting the quantity you want https://military-fasteners.com/clamps/ms21919WH14 and selecting the quantity you want https://military-fasteners.com/clamps/ms21919WH14 and selecting the quantity you want https://military-fasteners.com/clamps/ms21919WH14 and selecting the property of the selection of the property of t