

Description

diameter: 3/16", loop type, cushioned, 400ÅÅ□ Å~ÅÅ□ Å¿ÅÅ□ Å½, steel with silicone cushion, MS21919 series clamp

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------------------|
| SKU / Model: | MS21919WH3 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5340-00-598-8620 |
| Schedule B: | 7318.29.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 061200, Cable Clamps / Joints Noi |



* See page 2 for technical characteristics

P/N MS21919WH3 Specifications

| | |
|--|--|
| Tongue Hole Type: | Round, Unthreaded |
| Cushioning Environmental Protection: | Heat |
| Overall Width: | 0.375 Inches Nominal |
| Diameter: | 0.204 Inches Nominal |
| Material Thickness: | 0.029 Inches Minimum And 0.036 Inches Maximum |
| Center To Center Distance Between Loop And Mounting Hole: | 0.423 Inches Nominal |
| Distance From Loop Center To Tongue End: | 0.611 Inches Nominal |
| Loop Inside Diameter: | 0.173 Inches Minimum And 0.203 Inches Maximum |
| Material: | Rubber Cushion |
| Material: | Steel Band |
| Material Document And Classification: | Qq-s-636,cond 4 Fed Spec Single Material Response Band |
| Surface Treatment: | Cadmium Band |
| Style Designator: | Offset Mount |
| Nondefinitive Spec/std Data: | 3 Type And A Class |

How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919WH3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.