

Description

Diameter: 13/64", steel comp 321 band

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------|
| SKU / Model: | MS21919WH38 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5340-01-199-3465 |
| Schedule B: | 7318.29.0000 |
| ECCN: | 9A991 |
| National Motor Freight: | 095190, Hardware, Noi |



* See page 2 for technical characteristics

P/N MS21919WH38 Specifications

| | |
|--|---|
| Tongue Hole Type: | Round, Unthreaded |
| Cushioning Environmental Protection: | Corrosion Resistant And Weather Resistant And Oil Resistant |
| Overall Width: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Diameter: | 0.199 Inches Minimum And 0.209 Inches Maximum |
| Material Thickness: | 0.040 Inches Nominal |
| Center To Center Distance Between Loop And Mounting Hole: | 1.648 Inches Minimum And 1.678 Inches Maximum |
| Distance From Loop Center To Tongue End: | 1.851 Inches Minimum And 1.911 Inches Maximum |
| Loop Inside Diameter: | 2.360 Inches Minimum And 2.390 Inches Maximum |
| Material: | Rubber Silicone Class Q Cushion |
| Material: | Steel Comp 321 Band |
| Material Document And Classification: | Ams 3303 Assn Std Single Material Response Cushion |
| Material Document And Classification: | Ams 5510 Assn Std Single Material Response Band |
| Surface Treatment: | Passivate Band |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Band |
| Style Designator: | Offset Mount |

How to Order

Order this clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919WH38> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.