

**Description**

tube outside diameter: 3/16", carbon steel, sleeve coupling, flareless

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS219213
Minimum Qty (MOQ):	5
NSN:	4730-00-289-8637
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N MS21921-3 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Fabrication Method:</b>	Machined
<b>Nut Style:</b>	Tube Coupling
<b>Nut Height:</b>	0.578 Inches Nominal
<b>Width Across Flats:</b>	0.438 Inches Nominal
<b>Length To Shoulder:</b>	0.422 Inches Minimum And 0.438 Inches Maximum
<b>Smallest Inside Diameter:</b>	0.230 Inches Minimum And 0.245 Inches Maximum
<b>Thread Series:</b>	Unf
<b>Thread Quantity Per Inch:</b>	24
<b>Nominal Thread Size:</b>	0.375 Inches
<b>Nominal Tube Outside Diameter:</b>	0.188 Inches
<b>Seat Angle:</b>	45.00 Degrees Nominal
<b>Material:</b>	Steel Comp 1137 Overall Or Steel Comp 1141 Overall
<b>Material Document And Classification:</b>	66,aisa/sae 1137 Or 1141 Fed Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	96906-ms21921 Government Standard

## How to Order

Order this tube coupling nut from our inventory online by visiting <https://military-fasteners.com/nuts/tube+coupling+nuts/MS21921-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.